



ERS-200-F

FIBRATED ASPHALT EMULSION

FIBRATED ASPHALT EMULSIONS

ENVIRONMENTALLY SAFE COATING SYSTEMS

ERS-200-F Asphalt Emulsions is a water-based coating that offers low-cost, environmentally safe, fire retardant waterproofing protection over existing roofing or masonry waterproofing applications. The high solids formulation of this product includes a high-grade, non-volatile asphalt binder, water, and mineral colloids that are carefully blended to achieve a uniform paint-like consistency. ERS-200-F has proprietary, non-asbestos mineral fibers and special fillers added to provide additional coating strength. With a high solids content, the material will cure quickly, leaving a tough, flexible surface which provides greater retained coating thickness than most conventional emulsions. The surface offers resistance to chemicals, biological and ultra-violet degradation. ERS-200-F meets ASTM D 1227 Type IV (non-asbestos) and comply with all VOC requirements.

SPRAY APPLICATION PROVIDES QUICK LOW-COST APPLICATIONS

ERS-200-F is a premium-grade emulsion which can be used very effectively as protective coating for new or remedial restoration of smooth surface asphalt and modified roof systems or, for above and below grade masonry waterproofing applications. Application is by means of brush or spray over a clean surface. Where a porous or dusty surface exists, the substrate should be primed with Ecology's ERS-301 Asphalt Primer. Coverage rates for the emulsion application will vary depending on the surface and specification, and whether a reinforcing membrane, such as Ecology's ERS-310 Polyester Mat, ERS-311 Fiberglass Mat or ERS-312 Scrim, is to be sandwiched between applications of the emulsion. ERS-200F should not be applied when rain is imminent. The cured emulsion may be coated with one of Ecology's white or aluminum reflective coatings or covered with ceramic granules or roofing gravel.

GENERAL DATA

Color:	Black (Cured)	
Application Rate:	Approx. 3 gal. per 100 sq. ft. without reinforcement, to 8 gal. per 100 sq. ft. with reinforcement	
Container Sizes:	5 gal	55 gal
Weight:	47.5 lbs	522.5 lbs
Pallet Size:	36 pails	



Ecology Roof Systems®

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.