



ERS-300

ASPHALT MASTIC



MULTIPURPOSE ASPHALT MASTIC

ASBESTOS-FREE HEAVY DUTY REPAIR MASTIC

Ecology's ERS-300 Asphalt Mastic is an asbestos free, PROFESSIONAL GRADE, multi-purpose roof repair mastic which achieves a tenacious bond to the surface it is installed over, remaining pliable for years. Heavily fibrated with strong fiberglass fibers, mineral stabilizers, and the finest roofing asphalts, ERS-300 gives long-term security when making critical roof repairs, providing superior performance over conventional roof repair cements. ERS-300 meets Federal Specification SS-C-153C, Type 1 and ASTM D 4586 for asbestos-free products, while also meeting most existing VOC requirements.

BUTTERY CONSISTENCY PROVIDES EASY APPLICATION

ERS-300 can be applied to a clean, dry surface with a standard margin trowel. The smooth, buttery consistency of ERS-300 allows an easy, quick application. If the surface is porous or somewhat dusty, it is recommended that the surface be primed with Ecology's ERS-301 Asphalt Primer. Coverage rates will vary depending on the roughness of the substrate, the applied thickness and width of the material. ERS-300 is typically used as a general purpose repair mastic on asphalt-based roof systems for repairing mat blisters, ridges, open seams, and holes. It may also be used for small repairs to flashings or other components where a black repair mastic is acceptable. ERS-300 should have one of Ecology's polyester, or fiberglass reinforcing membranes embedded into the still fresh mastic, with the reinforcement covered with a second troweled application of ERS-300.

GENERAL DATA

Color:	Black
Coverage Rate:	Differs with porosity of surface and thickness of application.
Container Size:	5 gal
Weight:	53 lbs
Pallet Size:	36 pails



Ecology Roof Systems®

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.