



ERS-303-U

MULTIPURPOSE 1-PART SEALANT



TENACIOUS EXTERIOR GRADE SEALANT

SUPERIOR ELASTICITY FOR TOP PERFORMANCE

Ecology's ERS-303-U is a versatile, one-part polyurethane sealant designed for exterior use. Ecology's ERS-303-U is a non-sag formulation that provides exceptional adhesion qualities over a wide variety of building surfaces including concrete, stucco, masonry, metal, glass, and wood. Plasticizers and anti-oxidants are added to enhance long-term, non-cracking flexibility and give ERS-303-U excellent ultraviolet resistance. ERS-303-U contains no asbestos fillers and meets most existing VOC standards.

Typical uses include repair and/or sealing of reglet joints, open metal edge overlaps, sealing of pitch pans, sealing cracks in stucco walls, concrete, or windows.

EASY TO APPLY AND CLEAN UP

ERS-303-U should be applied to a clean, dry surface with a conventional gun, commercial caulking gun, or by trowel. Coverage rates will vary depending on the roughness of the substrate and the desired finished thickness of the sealant. For use on non-porous surfaces such as metal or glass, cleaning with MEK is recommended before application of ERS-303-U. ERS-303-U is best applied at temperatures below 100°F. For areas where the finished thickness of the sealant is to exceed 1/2", Ecology Closed-Cell Joint Backing is recommended.

GENERAL DATA

Application Rate:	12 linear feet per 1/2" x 1/4" bead	
Container Size:	12-11 oz. tubes per case	5 gal
Weight:	15 lbs	68 lbs
Colors:	Concrete Grey, Aluminum Grey, Limestone, White, Tan, and Off-White. Special colors on request	

Ecology Roof Systems®

Corporate Offices
 1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835
 PHONE: 800 553-3833 FAX: 714 526-1034
www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.