



## ERS-400-6

PREMIUM BUR PLY SHEETS

# PREMIUM FIBERGLASS REINFORCED PLY SHEETS

### PREMIUM GLASS PLY SHEETS

Ecology's ERS-400-6 offers a superior method of providing extra strong, lightweight, and rot resistant multiple base plies under an Ecology modified cap membrane or for use within one of Ecology's hot applied built-up roof systems. ERS-400-6 has a uniformly porous glass fiber mat that is coated with asphalt. The membrane meets ASTM D2178-88 Type IV. ERS-400-6 has a heavier-weight glass mat which is also coated with asphalt and offers approximately 35% more strength than ERS-400. ERS-400-6 meets ASTM D2178-88 Type VI.

ERS-400-6 is considered UL Type G-1 felts. The membranes have a lightly dusted surface providing excellent adhesion during installation.

### APPLICATION STANDARDS

The ERS-400-6 Ply Sheet can be installed with Ecology's ERS-All Temp and ERS-Hot Flex modified asphalt. It can be incorporated into several of Ecology's built-up and modified cap membrane roof specifications. The ERS-400-6 rolls have multiple guideline markings for ease of installation for the varied side-overlap requirements found within many specifications.

### GENERAL DATA

Membrane Type	Type VI
Roll Dimensions	3' x 180'
Roll Net Coverage	5 square
Rolls Per Pallet	20 rolls
Roll Weight	50 lbs.



**Ecology Roof Systems®**

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

www.ecologyroof.com