



## ERS-400

BUILT UP ROOF SYSTEM PLY SHEETS



# PREMIUM FIBERGLASS REINFORCED PLY SHEETS

### ECONOMICAL GLASS PLY SHEETS

Ecology's ERS-400 offers an economical method of providing multiple base plies under an Ecology modified cap membrane or for use within one of Ecology's hot applied built-up roof systems. Membranes are lightweight and rot resistant. ERS-400 has a uniformly porous glass fiber mat that is coated with asphalt. The membrane meets ASTM D2178-88 Type IV.

ERS-400 is considered UL Type G-1 felts. The membranes have a lightly dusted surface providing excellent adhesion during installation.

### APPLICATION STANDARDS

ERS-400 Ply Sheets can be installed with Ecology's ERS-All Temp and ERS-Hot Flex Modified Asphalt. They can be incorporated into several of Ecology's built-up and modified cap membrane roof specifications. ERS-400 rolls have multiple guideline markings for ease of installation for the varied side-overlap requirements found within many specifications.

### GENERAL DATA

Membrane Type	Type IV
Roll Dimensions	3' x 180'
Roll Net Coverage	5 square
Rolls Per Pallet	20 rolls
Roll Weight	45 lbs.



**Ecology Roof Systems®**

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

[www.ecologyroof.com](http://www.ecologyroof.com)