



## ERS-400(T)

COAL TAR PITCH SATURATED GLASS FELT

# FIBERGLASS REINFORCED COAL TAR PLY SHEETS

### ECONOMICAL GLASS COAL TAR PLY SHEETS

Ecology's ERS-400(T) offers an economical method of providing multiple base plies within Ecology's coal tar pitch built-up roof systems. Membranes are lightweight and rot resistant. ERS-400(T) has a uniformly porous glass fiber mat that is saturated with coal tar specifically blended for thorough and even penetration. The rolls are marked with ply lines for 2, 3, 4, and 5 ply BUR assemblies. The membrane meets ASTM D-4990 Type I.

The membranes have a lightly dusted surface providing excellent adhesion during installation.

### FEATURES

For over a century coal tar has proven itself to be a superior waterproofing substance. The self-healing characteristic of coal tar contributes to the excellent reputation this product has for longevity, and low maintenance cost.

### APPLICATION STANDARDS

ERS coal tar saturated felts, when used with ERS-Coal Tar should not be applied to roofs with slopes greater than 1/2" per foot. It is important that the installer completely overlay, in shingle fashion, each ply to the desired line. To assure long service life, each ply of ERS-Organic Felt must be completely encapsulated in coal tar roofing pitch, such as ERS-Coal Tar.

### GENERAL DATA

Membrane Type	Type IV
Roll Dimensions	3' x 180'
Roll Net Coverage	5 square
Rolls Per Pallet	20 rolls
Roll Weight	60 lbs.

## *Ecology Roof Systems*<sup>®</sup>

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

[www.ecologyroof.com](http://www.ecologyroof.com)