



ERS-554 GR FR

GRANULE TOP, SANDED BOTTOM,
POLYESTER, MODIFIED CAP SHEET



SBS MODIFIED POLYESTER CAP SHEET W/ HIGH FIRE RESISTANCE

ERS-554 GR FR cap ply is composed of selected SBS modified bitumen applied onto a non-woven polyester reinforcement with sand on the underside and a colored granule topside surface. ERS-554 GR FR is specifically designed for higher fire resistance.

The ERS-554 GR FR field and flashing cap membrane ply is adhered to a properly prepared, clean, dry and/or primed (where required) base or ply membrane by using the ERS-ALL-TEMP, ERS-HOT-FLEX or standard hot asphalt, or ERS-302, ERS-309 cold applied adhesive.

ERS-554 GR FR manufactured to meet ASTM-D-6164, Type, Grade G.

GENERAL DATA

Roll Dimensions	39" x 33'
Roll Net Coverage	97.5 Sq.Ft.
Rolls Per Pallet	25 rolls
Roll Weight	113 lbs.



Ecology Roof Systems®

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

www.ecologyroof.com