



ERS-5600

TRAFFIC DECK SYSTEM

TOUGH, DURABLE FINISH FOR HIGH TRAFFIC AREAS

DESCRIPTION

ERS-5600 traffic deck is a two-component, liquid-applied, aliphatic polyurethane coating with 100% solids and zero VOCs. ERS-5600 traffic deck can be easily installed over virtually any properly prepared, high-traffic surface to provide a tenacious, durable waterproof protection.

FEATURES

ERS-5600 traffic deck is easy to install with rollers or squeegees and has virtually no odors. ERS-5600 traffic deck is designed for pedestrian or vehicular traffic and is ideally suited for walking decks, balconies, plazas, parking decks, and mechanical room floors.

INSTALLATION

ERS-5600 traffic deck should be applied to surfaces that are completely free of foreign matter and have been primed with ERS-5600 primer. After the ERS-5600 primer has completely cured, the fully-mixed ERS-5600 traffic deck should be evenly applied by roller or squeegee at a minimum coverage rate of 80 square feet per gallon. The ERS-5600 traffic deck should then be back-rolled with a roller to break air bubbles. After a minimum cure time of 24 hours, a second application of ERS-5600 traffic deck should be installed at the same coverage rate. While the second application of ERS-5600 is still fresh, specified aggregate should be evenly broadcast into the ERS-5600 traffic deck to achieve the desired level of skidproofing. After a minimum cure time of 24 hours, the excess aggregate should be removed from the surface and a final application of ERS-5600 traffic deck should be installed at the same coverage rate.

GENERAL DATA

Colors	Concrete Gray, Tan, or Custom by special order	
Container Sizes	1.5 gal	4.5 gal
Weight	16 lbs	48 lbs

Ecology Roof Systems®

Corporate Offices
 1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835
 PHONE: 800 553-3833 FAX: 714 526-1034
www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.