



ERS-8000-FL-R & ERS-8000-FL-U

ELVALOY FLASHING SHEETS REINFORCED / UNREINFORCED

ELVALOY FLASHING SHEETS FOR ALL TYPES OF ROOF DETAILS

DESCRIPTION

Ecology Roof Systems ERS-8000 Flashing Sheets are elvaloy sheet materials cut into smaller widths than standard ERS-8000-FB or ERS-8000-MA sheets to assist in the waterproofing all types of roof perimeters or penetrations. The rolls can be ordered with (reinforced, ERS-8000-FL-R) or without (unreinforced, ERS-8000-FL-U) the polyester scrim.

APPLICATION

The ERS-8000-FL-R and ERS-8000-FL-U sheets **do not** have a fleece backing, allowing them to be adhered to the ERS-8000-FB or ERS-8000-MA field sheet by heat welding or with ERS-8001 Flashing Adhesive.

GENERAL DATA

Color White

REINFORCED (ERS-8000-FL-R)

Dimensions 39 in X 90 ft X 60 mil Weight 120 lbs Rolls Per Pallet 20

UNREINFORCED (ERS-8000-FL-U)

Dimensions 2.5 ft X 81 ft X 45 mil Weight 65 lbs Rolls Per Pallet 50

Ecology Roof Systems®

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.