



ERS-8007

ELVALOY WALK TREAD

ELVALOY WALK TREAD

DESCRIPTION

ERS-8007 Elvaloy Walk Tread is designed to be a rugged slip-resistant surface that will protect the ERS-8000 Elvaloy Sheet from damaging foot traffic. Around rooftop equipment ERS-8007 can be used to protect the field membrane from damage during maintenance work. The low-profile herringbone tread offers excellent traction, while allowing free drainage over its surface. The gray color stands-out from the white field sheet enough to define walking and working areas, without disrupting the aesthetics of the roof.

INSTALLATION

ERS-8007 Elvaloy Walk Tread should be installed with no continuous piece longer than 10 feet. There should be a 2" gap between the pieces of Walk Tread. The ERS-8007 Elvaloy Walk Tread can be either hot-air welded to the Elvaloy field sheet, or adhered with ERS-8001 Flashing Adhesive. If using adhesive, leave a 2" margin around the edge of the ERS-8007 Elvaloy Walk Tread free of adhesive for hot air welding.

Physical Properties

Walk pad dimensions	30" x 60'
Color	Gray

Ecology Roof Systems®

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.