



ERS-920-75



SELF-STICK PITCH-MODIFIED ELVALOY MEMBRANE

ADVANCED PITCH-MODIFIED ELVALOY SELF-STICK MEMBRANE

ERS-920-75 OFFERS AN ADVANCEMENT IN MODIFIED ROOFING

Ecology's ERS-920-75 belongs to a new generation of self-stick elastomeric sheet membranes. The ERS-920-75 membrane is a blend of DuPont's Elvaloy® KEE polymer, coal tar pitch, and dispersed polyester fibers. The membrane is manufactured with strict quality control that insures consistency of membrane thickness, and adhesive quality. As a weathering membrane, ERS-920-75 has the strength to shield underlying roofing assemblies from environmental, chemical, ultraviolet, and fungal degradation. ERS-920-75 is advantageous when either a smooth uncoated, coated, or flood coat and aggregate surface is required. When used in a smooth surface application, ERS-920-75 stands up to the normal scuffs and abrasions of a roof environment.

INSTALLATION

Self-stick installation is an advantage when specifying a roof system for a building owner sensitive to equipment noise, clutter, business disruption, fire hazards, or fumes -- schools, hospitals, malls, etc. The membrane courses can be seamed with four-inch laps, or butt joints. If butt joints are required, use ERS-900-CS Cover Strip, can be set in hot adhesive, or hot air welded into place.

LIMITATIONS

If installing ERS-920-75 over an existing asphalt or coal tar pitch roof, use ERS-Insulation, or ERS-Recover-Board to provide a separation between the old and new roofs, then prime the surface with ERS-Clear-Primer to achieve a good bonding surface. Do not use coal tar mastic or adhesives with ERS-920-75 due to solvents in these products, and incompatible flow characteristics. Do not use cold-applied cutback adhesives with ERS-920-75.

GENERAL DATA

Surface	Smooth
Bottom	Adhesive
Color	Black
Thickness	60 mil + 15 mil adhesive
Roll Coverage	1.5 square
Weight	82 lbs. per roll
Rolls Per Pallet	24



Ecology Roof Systems®

Corporate Offices
 1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835
 PHONE: 800 553-3833 FAX: 714 526-1034
www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.