



ERS-ALL TEMP ASPHALT

HOT BITUMEN



SUPERIOR WATERPROOFING ALTERNATIVE FOR BUILT-UP ROOF APPLICATIONS

DESCRIPTION

ERS-All Temp is a special blend of asphalts for use as a superior interply waterproofing adhesive in built-up roof construction. ERS-All Temp creates a weathering resistant system.

FEATURES

ERS-All Temp is manufactured to meet all ASTM D-312 performance criteria. ERS-All Temp is available in four basic grades and is specified according to slope requirements.

APPLICATION

ERS-All Temp can be heated using conventional, direct-heated roofing kettles and is applied using standard handling and mopping techniques. ERS-All Temp can be used with all types of conventional asphalt roofing felts and systems as well as modified base, ply, and cap membranes.

SPECIFICATIONS

Meets and exceeds ASTM D-312 test results. ERS-All Temp is available in four grades: Type I, II, III, IV

STORAGE

Protect from long exposure to direct sunlight, provide sufficient ventilation. Containers must be upright.

GENERAL DATA

Color	Black
Application Rate	25 lbs per square
Container Sizes	100 lb keg

Ecology Roof Systems®

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.