



ERS-CLEAR PRIMER

WATER-BASED CLEAR PRIMER



WATER-BASED CLEAR PRIMER PROVIDES SUPERB ADHESION

NON-FIBRATED, WATER BASED PRIMER

Ecology's ERS-Clear Primer is a premium grade, non-fibrated, quick drying, water based primer that can be applied to almost any surface and is virtually odor free. ERS-Clear Primer is used to provide increased adhesion over a variety of low-tack or slightly contaminated surfaces where calking, asphalt roof mastics, roof elastomers, protective/reflective coatings, modified bitumen membranes, self-adhered, single-ply membranes are to be applied. ERS-Clear Primer is quick drying, asbestos free, and with no VOCs.

ERS-Clear Primer is superior to asphalt cutback primers when used with protective/reflective coatings because the lack of solvents eliminates the possibility of incompatibility and or discoloration.

QUICK APPLICATION

ERS-Clear Primer can be applied to a clean, dry surface by brush, roller, or spray application. Coverage rates will vary with the porosity of the surface and the porosity of the substrate it is applied over. ERS-Clear Primer should be allowed to dry tack-free before applying additional repair materials, roof coatings, or roof membranes.

GENERAL DATA

Color	Milky White	
Application Rate	Smooth Surface:	Approx. 1/2 - 3/4 gal. per 100 sq. ft.
	Rough Surface:	Approx. 3/4 - 1-1/2 gal. per 100 sq. ft.
Container Sizes	5 gal	55 gal
Weight	43 lbs	450 lbs
Pallet Size	36 pails	

Ecology Roof Systems®

Corporate Offices
 1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835
 PHONE: 800 553-3833 FAX: 714 526-1034
www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.