



ERS-M10

WHITE REPAIR MASTIC



WHITE WATER BASED ELASTOMER

FOR ROOF REPAIRS REQUIRING SUPER ELASTICITY

With 10% more solids than most competitive products, Ecology's ERS-M10 Roof Elastomer quickly develops a tenacious, rubber-like, monolithic seal over the surface to which it is bonded. The elastomeric compound is specially blended to give it greater elongation and excellent recovery characteristics. ERS-M10 retains its non-crack flexibility down to subzero temperatures and retains its ultraviolet resistance for years, making it a highly effective repair material for the most troublesome of roof conditions. ERS-M10 will keep on performing when others have failed.

Ecology's ERS-M10 Elastomeric Mastic contains no asbestos fillers and meets existing VOC standards, (ERS-M10 is for surface application only).

EASY TROWEL APPLICATION

ERS-M10 can be applied to a clean, dry surface with a trowel or brush. If the surface is porous or somewhat dusty, it is recommended that the surface be primed with Ecology's ERS-301 Asphalt Primer. Coverage rates will vary depending on the roughness of the substrate and the thickness of the material. ERS-M10 can be applied to vertical and horizontal asphalt based roofing materials, concrete, masonry and metal surfaces. Typical applications include the repair or sealing of flashing holes and open seams, open metal edge overlaps, pitch pans, or other areas where dissimilar materials meet and require added strength and elongation capabilities. ERS-M10 can also be used on seam overlaps and details with Ecology's self-adhered roofing membranes.

GENERAL DATA

Color	White
Application Rate	Approximately 3.5 linear feet per gal. at 1/4" thick
Container Size	3 1/2 gal
Weight	44 lbs
Pallet Size	36 pails

Ecology Roof Systems®

Corporate Offices

1400 North Harbor Blvd. Suite #601, Fullerton, CA 92835

PHONE: 800 553-3833 FAX: 714 526-1034

www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.