

MIXING INSTRUCTIONS:

Thoroughly mix the Part B (1 pint can) and pour contents into Part A (1 gallon can). Thoroughly stir components together using a variable speed drill and mixing blade for a minimum of 5 minutes. Be sure to scrape the sides of the can to ensure uniform mixing. Note: Part B (1 pint can) may be pressurized – open container slowly.

Note: When mixed, Pourable Sealer has a pot life of approximately 30 minutes.

INSTALLATION:**A. Pitch Pans**

Fit the EPDM membrane as tightly as possible around the penetrating object and seal as necessary to prevent loss of filler. Install and flash pitch pans in accordance with the appropriate details. Minimum Pourable Sealer depth required is 2 inches. Minimum distance from object to the side of the pans is 1 inch. Clean all mating surfaces with specified cleaner and fill pan with properly mixed Pourable Sealer in sufficient quantity to crown the top surface to prevent ponding water.

B. Tie-in to Built-Up Roof Surfaces

Scrape and clean the built-up surface to remove all gravel, dirt and moisture in the tie-in area to ensure the surface is smooth, clean and dry. When properly mixed, apply the ERS-EPDM Pourable Sealer as specified and embed the Uncured EPDM Flashing as shown in the detail section of the Ecology Roof Systems Manual.

PRECAUTIONS:

ERS-EPDM Pourable Sealer contains ingredients that could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. Ecology Roof Systems maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Ecology Roof Systems' Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Ecology Roof Systems products in your facilities.

Ecology Roof Systems®

Corporate Offices: 9821 Olde Eight Road, Unit F, Northfield, OH 44067

PHONE: 330-467-4220 FAX: 330-467-4225 www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Ecology Roof Systems to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Ecology Roof Systems. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY ECOLOGY ROOF SYSTEMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.