



PRODUCTS FOR OUR ENVIRONMENT

## TECHNICAL DATA SHEET

### ERS-EPDM Sealant Pockets

For Professional Use Only



#### PRODUCT DESCRIPTION:

ERS-EPDM Sealant Pockets are prefabricated pockets consisting of a 2" (50 mm) wide plastic support strip with uncured EPDM flashing tape attached.

#### USES:

ERS-EPDM Sealant Pockets are ideal for sealing irregular, hard to flash penetrations through the membrane.

#### PHYSICAL CHARACTERISTICS:

|             |                                                                                  |
|-------------|----------------------------------------------------------------------------------|
| Sizes:      | 4", 6", and 8" Diameter (several pockets can be combined to form larger pockets. |
| Packaging:  | 12 per carton                                                                    |
| Weight:     | 5 lbs. / ctn for 4" - 7 lbs. / ctn for 6" - 9 lbs. / ctn for 8"                  |
| Color:      | Black                                                                            |
| Shelf Life: | Nine (9) months when stored between 60°F - 80°F (15°C - 26°C)                    |

#### PACKAGING & STORAGE:

Keep the material clean. Materials should be stored in a cool dry location.

#### INSTALLATION:

- See appropriate installation guidelines.
- Pockets can also be stacked two high if necessary to achieve a greater height.
- A heat gun may be required for forming outside in colder temperatures

#### PRECAUTIONS:

Job site storage temperatures in excess of 90°F (32°C) may affect the shelf life of the product.  
180°F (82°C) maximum temperature

Pourable Sealant must contact Uncured Flashing Tape and deck membrane

Pourable Sealant Pocket to be 1" minimum from penetration on any side

Pourable Sealant must completely fill pocket to prevent ponding water

Additional securement is required for pockets greater than 18" (460 mm) in diameter.

Pourable Sealant to be a minimum of 2" (50 mm) deep.

***Ecology Roof Systems®***

Corporate Offices: 9821 Olde Eight Road, Unit F, Northfield, OH 44067

PHONE: 330-467-4220 FAX: 330-467-4225 [www.ecologyroof.com](http://www.ecologyroof.com)

#### REGIONAL OFFICES LOCATED ACROSS THE U.S.

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Ecology Roof Systems to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Ecology Roof Systems. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY ECOLOGY ROOF SYSTEMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.