



PRODUCTS FOR OUR ENVIRONMENT

TECHNICAL DATA SHEET

ERS-TPO Clad Metal

For Professional Use Only

PRODUCT DESCRIPTION:

ERS-TPO Clad Metal is a galvanized steel sheet that is coated with a layer of non-reinforced TPO flashing.

USES:

ERS-TPO Clad Metal is cut into the appropriate width and used to fabricate metal drip edges or other roof perimeter edging profiles. TPO membrane may be welded directly to the coated metal edging, eliminating the need to strip in the metal with a separate piece of membrane..

PHYSICAL PROPERTIES:

Sheet Size	4 foot by 10 foot (1.2m by 3.0 m)
Weight	1.1 lb/ft ² (5.4 kg/m ²)
Color	Gray, Tan and White
Flashing Thickness	0.035 inches (0.9 mm) nominal
Steel Thickness	0.024 inches (0.6 mm) nominal (24 gauge)
Steel Type	Hot Dipped Galvanized Steel – G90
Packaging	10 or 25 sheets per pallet

PACKAGING & STORAGE:

Store flat in a cool, dry area.

PRECAUTIONS:

ERS-TPO Clad Metal that has been exposed to the weather for approximately 7 days or longer prior to use must be prepared with ERS-Weathered Membrane Cleaner prior to hot air welding.

Ecology Roof Systems®

Corporate Offices: 9821 Olde Eight Road, Unit F, Northfield, OH 44067

PHONE: 330-467-4220 FAX: 330-467-4225 www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Ecology Roof Systems to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Ecology Roof Systems. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY ECOLOGY ROOF SYSTEMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.