



PRODUCTS FOR OUR ENVIRONMENT

TECHNICAL DATA SHEET

ERS-920-75 Flashing

P/N: 035-0105

P/N: 035-0106

For Professional Use Only



SELF-STICK PITCH-MODIFIED ELVALOY MEMBRANE FLASHING.

PRODUCT DESCRIPTION:

ERS-920-75 Flashing is Ecology's ERS-920-75 roofing sheet cut to 9" and 12" widths. The ERS-920-75 Flashing membrane is a blend of DuPont's Elvaloy® KEE polymer, coal tar pitch, and dispersed polyester fibers. The membrane is manufactured with strict quality control that insures consistency of membrane thickness, and adhesive quality. As a weathering membrane, ERS-920-75 Flashing has the strength to shield underlying roofing assemblies from environmental, chemical, ultraviolet, and fungal degradation.

APPROVALS:



PACKAGING

ERS-920-75 Flashing comes in 9" x 50' roll (.229 m x 15.24 m), or 12" x 50' roll (.305 m x 15.24 m).

PHYSICAL PROPERTIES:

Property	Typical Value	Test Method
Elongation	170%	ASTM D 412
Tensile Strength	1500 lbs/in ²	ASTM D 412
Tear Strength	300 ppi	ASTM D 624
Low Temp Flexibility	Pass	37-GP-56M
Water Absorption	<0.1%	37-GP-56M
Thickness	60 mil + 15 mil adhesive	
Weight	82 lbs. (27.23 kg)	
Net Coverage	150 ft ² /roll net (13.94 m ²)	

Ecology Roof Systems®

Corporate Offices

9821 Olde Eight Road, Unit F, Northfield, OH 44067

PHONE: 330-467-4220 FAX: 330-467-4225

www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Ecology Roof Systems to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Ecology Roof Systems. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY ECOLOGY ROOF SYSTEMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.