



## ERS-Clear Primer

P/N: 015-0010

For Professional Use Only



### PRODUCT DESCRIPTION:

ERS-Clear Primer is a quick-drying, totally VOC compliant primer that improves the adhesion of self-adhering membranes, asphaltic coatings and repair materials to asphalt, concrete and aged metal surfaces.

### RECOMMENDED USES:

ERS-Clear Primer can be used as a primer on a variety of substrates prior to the application of many Ecology products to promote excellent adhesion. Contact Ecology Technical Services with questions.

### ADVANTAGES:

- Rapid drying.
- Contains no asbestos.
- Solvent-free.
- Meets all VOC requirements.
- Promotes adhesion to many substrates encountered in roofing applications.

### INSTALLATION: Do not thin.

**Surface Preparation:** All loose gravel must be removed from roof. All surfaces should be clean and dry prior to application.

**Application:** Do not thin. ERS-Clear Primer may be applied by brush, roller or low-pressure spray.

**Drying Time:** Depending on the rate of application, porosity of surface and drying conditions, ERS-Clear Primer will dry in one to four hours.

### COVERAGE RATE:

ERS-Clear Primer is applied at a nominal rate of 200 square feet per gallon. Application rate will vary with substrate surface conditions.

### PACKAGING:

ERS-Clear Primer is available in 5 gallon (18.9 liter) pails.

### STORAGE LIFE:

One year from date of shipment when stored in original, unopened containers. Keep from freezing.

### PRECAUTIONS:

- DO NOT THIN.
- Do not use on new metal.
- Do not allow to freeze.

**PHYSICAL PROPERTIES:**

Property	Typical Value	Test Method
Volatiles by Volume	75%	ERS Test
Specific Gravity	1.22	ASTM D 1475
Viscosity	60 – 70 KU	ASTM D 562
Percentage Solids by Weight	38.7%	ASTM D 1644
Asbestos Content	0%	EPA 600/R-93/116

## *Ecology Roof Systems*®

Corporate Offices

9821 Olde Eight Road, Unit F, Northfield, OH 44067

PHONE: 330-467-4220 FAX: 330-467-4225

[www.ecologyroof.com](http://www.ecologyroof.com)

REGIONAL OFFICES LOCATED ACROSS THE U.S.

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Ecology Roof Systems to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Ecology Roof Systems. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY ECOLOGY ROOF SYSTEMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.