



## ERS-EcoSheen

P/N: 035-0115

For Professional Use Only



### PRODUCT DESCRIPTION:

ERS-EcoSheen is a water-based, penetrating sealer designed to produce a clear, semi-gloss surface sheen. It is manufactured from non-yellowing, advanced acrylic resins to form a durable finish that provides long-term water-repellency, dirt and moderate graffiti resistance, and weather protection.

ERS-EcoSheen's low viscosity allows it to "wet in" and lock into the substrate. It will allow moisture vapor to escape from the building interior, yet provides excellent damp-proofing characteristics on the exterior. The appearance will remain uniform, eliminating any blotchiness from water staining, even after years of service.

### RECOMMENDED USES:

ERS-EcoSheen was specifically developed as a penetrating sealer for use over properly prepared smooth or textured concrete, exposed aggregate concrete, brick, stone or stucco surfaces where a semi-gloss sheen is desired. It also has the durability required for use over exposed aggregate and other surfaces on vertical or horizontal applications.

ERS-EcoSheen imparts a slick, semi-gloss film over a variety of substrates, providing for increased dirt pick-up and graffiti resistance. It can be used as a topcoat over numerous types of new or existing finishes on roofs, walls and decks to provide sheen, graffiti resistance and/or ease of cleanability. It is also effective in rejuvenating aged and/or oxidized skylights.

### ADVANTAGES:

- Facilitates graffiti removal
- Protects against industrial airborne chemicals
- Reduces soil and fume absorption
- Minimizes run-down discoloration
- Non-yellowing
- Prevents moisture staining of surfaces
- Minimizes efflorescence
- Excellent ultraviolet resistance
- Conforms to most VOC regulations
- Reduces spalling and deterioration
- Single package – No shelf or pot life problems
- Water-Based – No flammable solvents
- Long term durability

### COVERAGE:

Substrate	Square Feet/Gallon Substrate Estimated Total*
Concrete	125 to 150 (3.0 to 3.9 m <sup>2</sup> /l)
Exposed Aggregate	75 to 100 (1.8 to 2.4 m <sup>2</sup> /l)
Brick, Stone	125 to 150 (3.0 to 3.9 m <sup>2</sup> /l)
Stucco	60 to 75 (1.4 to 1.8 m <sup>2</sup> /l)
Existing Coating	150 to 250 (3.9 to 6.1 m <sup>2</sup> /l)

\*These estimates are totals for two separate applications. Apply approximately half the total number of gallons in each of the two coats. The above absorption (coverage) rates are provided for estimating purposes only. Coverage rates will vary with texture and porosity of the substrate. Allow for additional material when estimating coverage over highly textured or porous surfaces.

### PACKAGING:

ERS-EcoSheen is available in 5 gallon (18.9 liter) pails.

### STORAGE LIFE:

Storage life is 1 year in original unopened container.

### PRECAUTIONS & LIMITATIONS:

ERS-EcoSheen should not be applied over wet surfaces or wood substrates, however, concrete and masonry surfaces can be coated while slightly damp. In locations that are typically hot and arid, it can be beneficial to pre-dampen the surface prior to the application of ERS-EcoSheen. ERS-EcoSheen is a water-based sealer. Care must be taken during storage and shipment to ensure that temperatures do not fall below 32°F (0°C). Do not apply ERS-EcoSheen at temperatures below 50°F (10°C). Cool temperatures and high humidity will retard cure.

Avoid breathing of vapor or spray mist. Approved (MSHA/NIOSH) chemical cartridge respirator should be worn by applicator. For additional information on safety requirements, refer to OSHA guidelines and ERS-EcoSheen Material Safety Data Sheet.

#### **SURFACE PREPARATION:**

All surfaces must be structurally sound, clean, dry, fully cured, and free of dirt, dust, oil, curing or form release agents, efflorescence, scale, or other contaminants that could inhibit optimum adhesion. Existing coatings that are loose, cracked or peeling must be completely removed. ERS-EcoSheen is a penetrating sealer designed to wet into the surface to which it is applied. Surfaces such as glazed brick, smooth dense brick, glass fiber reinforced concrete, and dense, steel-trowelled concrete must be etched or abraded prior to application of ERS-EcoSheen to allow for maximum penetration. An adhesion enhancing additive is also available for application over tile and other slick surfaces. ERS-EcoSheen can be applied over most existing paints or coatings where additional sheen and/or cleanability is desired. As it will be unable to penetrate into the substrate on these applications, the existing finish must be sound and well adhered, as well as clean and dry.

#### **APPLICATION:**

ERS-EcoSheen shall be applied by airless spray equipment. Any airless spray equipment capable of 1,000 psi (6,980 kPa) and ½ gallon per minute (1.9 l/minute) delivery can be used for applying ERS-EcoSheen. For maximum production on large projects, airless spray equipment capable of 2,000 psi (13,780 kPa) and 1 gallon per minute (3.8 l/minute) delivery should be used. A reversible self-cleaning spray tip with orifice size of .013" to .017" (.330 to .425 mm) and minimum 40 degree fan angle is recommended. Brush or roller application is recommended only for edging work and for confined areas that would require extensive masking or protection from spray application.

ERS-EcoSheen shall be applied in two separate applications except where a single application gives the desired surface finish characteristics. When spraying, each application shall be first in a uniform horizontal direction, followed by a uniform overlapping vertical direction. Gun shall be held not more than 18" (45 cm) from wall. Care should be taken during application to prevent runs or sags. Thinning should not be necessary when applying ERS-EcoSheen over exposed aggregate or other similar surfaces. Over dense substrates it may be reduced with clean water to achieve the desired consistency for adequate penetration.

Other restoration work and caulking should be completed prior to application of the ERS-EcoSheen. Most standard caulking compounds are compatible with surfaces previously treated with ERS-EcoSheen, however, field testing should be performed for confirmation. Clean pump, tools and other equipment with fresh water. Flush water from the pump and hoses with Mineral Spirits for storage.

#### **GRAFFITI RESISTANCE:**

Successful removal of graffiti stains will vary greatly depending on type of graffiti material used, time that passes prior to cleaning and number of times graffiti is removed. ERS-EcoSheen will protect the substrate against atmospheric deterioration with a clear, semi-gloss film that provides water-repellency and surface sheen without significantly altering the natural color or texture of the substrate.

Ecology recommends that a sample test area be applied, and approval be obtained, prior to any general application of the material. ERS-EcoSheen may bring out the natural color of the particular concrete or masonry surface being sealed, resulting in a darkened appearance, as if wetted. Apply the test area on an inconspicuous area of the actual building to determine the optimum coverage rate to achieve uniformity of sheen, as well as to determine the suitability of the application technique.

#### **PHYSICAL PROPERTIES:**

Property	Value	Method
<b>Solids by Weight</b>	19% (±.5)	ASTM-D-2369
<b>Solids by Volume</b>	18% (±.5)	ASTM-D-2697
<b>Weight per Gallon</b>	8.5 lbs (±.2)	ASTM-D-1475
<b>Dry Time*</b>	1 hour	ASTM-D-1640
<b>Cure Time*</b>	3 hours	ASTM-D-1640
<b>Gloss</b>	85 (±5) (60° Gardner)	ASTM D523
<b>Flash Point</b>	>212°F (100°C)	ASTM D3278
<b>Low &amp; High Temp. Service Limits</b>	-40°F to 180°F (-40°C to 82°C)	

**Ecology Roof Systems**® Corporate Offices: 9821 Olde Eight Road, Unit F, Northfield, OH 44067

PHONE: 330-467-4220 FAX: 330-467-4225 www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Ecology Roof Systems to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Ecology Roof Systems. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY ECOLOGY ROOF SYSTEMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.