



## ERS-Retrofit Drains

P/N: 035-0135  
035-0136  
035-0137  
035-0138



### PRODUCT DESCRIPTION:

ERS-Retrofit Drains are constructed of aluminum and stainless steel for durability and designed for use with Single Ply, BUR & Modified Bitumen roofing systems. The patented backflow compression seal is compatible with PVC or cast iron leader pipes. This drain features an extra large flange for positive attachment of the roof flashing membrane, a recessed metal clamping ring for roof termination and proper drainage, along with an oversized drain strainer to minimize damming. Available in 3", 4", 5", and 6" sizes with the low profile strainer dome..

### FEATURES:

- Pre-punched .080" thick with a large 18" x 18" aluminum drain flange.
- 14" diameter .080" thick aluminum drain strainer dome.
- 9" long drain stem.
- Includes a .125" thick, aluminum clamping ring.
- Incorporates the patented backflow compression seal.
- Simple and easy to install from rooftop.

### ADVANTAGES:

- Drain flange insures consistent, stable attachment to the substrate outside of the existing drain bowl and positive attachment of flashing membrane.
- Strainer dome features a low profile base to promote drainage and the large diameter provides added flow capacity and minimizes damming.
- Drain stem accommodates most existing field conditions with various drain pipe lengths available for quick turn elbows or deep existing drain bowls.
- The aluminum clamping ring is recessed into the drain flange to maximize drainage and is secured to stainless steel studs.
- The RAC Backflow Compression Seal is quickly activated at drain flange level with any 7/16" wrench and protects the roofing system and building contents from water backup damage.
- Saves time and money because it allows easy rooftop installation without disturbing interior finishes or activities, eliminating the need to remove the old drain.

### PHYSICAL PROPERTIES:

Drain Body	.080" thick aluminum
Flange Width	18"x18" w/sump area
Stem Length	9"
Watertight Seal	Backflow compression requires 7/16" wrench
Clamp Ring	.125" thick aluminum recessed
Strainer Dome	14" diameter, 4" high Made of .080" thick aluminum

## Ecology Roof Systems®

Corporate Offices  
9821 Olde Eight Road, Unit F, Northfield, OH 44067  
PHONE: 330-467-4220 FAX: 330-467-4225  
www.ecologyroof.com

REGIONAL OFFICES LOCATED ACROSS THE U.S.

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Ecology Roof Systems to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Ecology Roof Systems. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY ECOLOGY ROOF SYSTEMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.